

ORA WIND SPEED SENSOR

IP 65
PROTECTION
RATING

AI
METAL
MATERIAL

0 - 2.5 V
ANALOG
OUTPUT

LP
LOW
POWER



Highly precise, robust

and professional are these new wind sensors of the ORA-family. The low power consumption of < 2 mA makes this sensor ideally suitable for solar powered applications. The sensor is completely made of metal and if necessary the cup rotor is easy to change in the field.

- 4...15 VDC
- low power consumption < 2 mA
- all-metal housing made of seawater resistant aluminium
- on site changeable cup rotor made of seawater resistant aluminium
- protection class IP 65 in upright position

APPLICATIONS

- small wind power plants
- professional weather stations
- agriculture
- solar powered applications

Professional Line	ORA
Id-No.	00.14594.210000
Measuring range	0,4...55 m/s
Accuracy	< ± 0,5 m/s
Resolution	< ± 0,1 m/s
Starting value	0.4 m/s
Output	0...2.5 V
Strongest wind impact velocity	80 m/s
Current consumption	< 2 mA (low power)
Measuring principle	magnetic
Dimensions	wind speed: cup rotor Ø 108 mm - H 192 mm
Housing	seawater resistant aluminium • IP 65 • for bores with Ø 30 mm at max. 10 mm material thickness • incl. plug connector
Weight	approx. 0.90 kg
Included in delivery	1 sensor • 12 m cable • with 4 pin M12 plug connector
Accessories (order separately)	Id-No. 32.14567.006000 Mast adapter Ø 50 mm • Id-No. 32.14627.010000 Wind traverse

As of: 23.10.2022